

EOS M6 MARK II



Fast, versatile and lightweight mirrorless camera—perfect for your travels

A stylish, compact and lightweight mirrorless camera that doesn't compromise on speed or quality whether you're shooting stills or movies. The EOS M6 Mark II features the option to add on an Electronic Viewfinder so you can shoot the way that feels most comfortable to you. Enjoy a high image quality with the camera's 32.5 megapixel APS-C sensor. Ensure you never miss the shot with a maximum continuous shooting speed of approximately 14 fps and a maximum RAW burst mode of approximately 30fps.

Quick upload and share

With integrated Wi-Fi and Bluetooth connectivity, you can share the images from your EOS M6 Mark II to your smart device quickly and easily with the Canon Camera Connect App. A constant connection between the EOS M6 Mark II and your smartphone can be maintained via Bluetooth® connectivity, letting you view your photographs without taking the camera from your bag.

Canon

EOS M6 MARK II

Dual Pixel AF
CMOS

Dual Pixel CMOS AF delivers fast and smooth AF as well as exceptional tracking performance when shooting in Live View and movie mode.

32.5 MEGA PIXELS
CMOS

TTL: 34.4 MP

Shoot your world with a brilliant 32.5 megapixel Canon CMOS sensor. The latest sensor provides stunning clarity and the freedom to crop.

4K

Enjoy shooting uncropped 4K 30p movies and time-lapse. The M6 Mark II also supports Full HD 120p/100p.

Upto
14
Frames
Per Sec

Upto
30
Frames
Per Sec
RAW Burst

The EOS M6 Mark II delivers high-speed continuous shooting at up to 14 fps whilst maintaining AF performance. You can also shoot up to 30 fps with in RAW burst mode.

DiGiC
8

Canon's DiGiC 8 image processor offers boosted image processing power for lower noise, more detail, richer tones and vastly improved subject tracking ability.


Eye Detection
AF

Eye detection Autofocus technology can be set during Servo AF (stills and movies) and ensures that the camera is locking in on your subjects eye and focusing to that point, even when they're moving around the frame.

3:2
WIDE

7.5cm / 3.0" LCD
ClearView II
Touch

The LCD monitor can tilt 180 degrees upwards and 45 degrees downwards enabling you to find your own unique angle or take the perfect selfie.

ISO
25600

Whether it's manipulating light or simply shooting in unusual conditions, with the ability to select ISO up to a massive 25,600 (ISO expansion 51,200 equivalent), the EOS M6 Mark II is the camera to be carrying for unique, well composed photographs.

RAW
JPEG
In-Camera
RAW processing

Convert images from RAW to JPEG in camera with the ability to change white balance or picture style settings. Multiple images can be converted in a batch for convenience.

Canon

Technical Specifications

EOS M6 MARK II

IMAGE SENSOR	
Type	APS-C CMOS
Effective Pixels	Approx. 32.5 megapixels
Total Pixels	Approx. 34.4 megapixels
Image Quality	L, M, S1, S2, RAW, C-RAW
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour
IMAGE PROCESSOR	
Type	DIGIC 8
LENS	
Lens Mount	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)
FOCUSING	
Type	Dual Pixel CMOS AF System
AF System/ Points	Maximum focusing area (approx., relative to capture image): Horizontal: 88%, Vertical: 100% Number of AF area available for automatic selection: Face+ Tracking AF: Max. 143 points. Selectable positions for AF point: Max. 5481 zones Max. number of AF points: (Same with number of AF area available: Max. 143)
Focusing brightness range	EV -5 - 18
AF Modes	One-Shot AF, Servo AF, Touch & Drag AF, Eye Detection AF (One-shot & Servo), Face & Tracking
AF Lock	Locked when shutter button is pressed half way, or via the AE lock button.
AF Assist Beam	via LED assist beam
Manual Focus	With EF & EF-S lenses - Select via AF/MF switch on lens With EF-M lenses - Select via dedicated MF Button/ other customisable buttons (toggle AF/MF). MF Peaking available: Available (Level: High/Low, Colour Red/Yellow/Blue)
EXPOSURE CONTROL	
Metering modes	384-zone (24 x 16) metering with image sensor. Center-weighted average metering; Supported Evaluative metering; Supported
Metering Range	Still image: EV -2 - 20 Movie: EV 0 - 20
AE Lock	Stills: Auto/Manual Movie: Manual
Exposure Compensation	+/-3 EV in 1/3 stop increments or 1/2 stop increments
AEB	+/-3 EV in 1/3 stop increments or 1/2 stop increments
ISO Sensitivity	STILLS: Creative Zone - ISO Auto: 100-25600 - Manually set: 100-25600, H (equivalent to ISO 51200) Basic Zone - ISO Auto: Varies by shooting mode MOVIES: Shooting with auto exposure -ISO Auto: 100-12800 (expanded in Creative Zone) Shooting with manual exposure -ISO Auto: 100-12800 -Manually set: ISO 100-12800
SHUTTER	
Type	Electronically controlled focal-plane shutter
Speed	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)
WHITE BALANCE	
Type	Auto white balance with the imaging sensor
Settings	Auto (Ambiance priority), Auto (white priority), Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom, Colour temperature settings (approx. 2500-10000K). White balance correction and white balance bracketing features provided.

VIEWFINDER	
Type	Optional Electronic Viewfinder EVF-DC1, EVF-DC2 (included)
Viewfinder Information	With EVF-DC2: Customisable and toggle via INFO. Button (1) Liveview image with exposure info (2) Liveview image with basic info (3) Liveview image with full info Customisable settings: Shooting Info, Grid overlay (x3 formats), Histogram (Brightness/RGB), Electronic Level, Aspect Ratio
Depth of field preview	Yes, via customisable buttons
LCD MONITOR	
Type	7.5 cm (3.0") ClearView II Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Tiltable 180 degrees up and 45 degrees down.
Touch Shutter	Available
Coverage	Approx. 100%
Brightness Adjustment	Adjustable to one of seven levels
FLASH	
Built-in Flash GN (ISO 100, meters)	4.6
Built-in Flash Coverage	Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm)
Red-Eye Reduction	Yes - with red eye reduction lamp
X-sync	Yes
Flash Exposure Compensation	+/- 2 EV in 1/3 or 1/2 stop increments
Retraction Method	Manual pop-up flash (auto pop-up not included)
Recycle time	Approx 4 seconds
External Flash Compatibility	EL and EX series Speedlites
External Flash Control	Via camera setting/ flash setting menu
SHOOTING	
Modes	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN(Self-Portrait, Portrait, Landscape, Close-up, Sports, Food, Panning, Handheld Night Scene, HDR Backlight Control), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Art bold effect, Water painting effect, Toy camera effect, Miniature effect), Program AE, Shutter priority AE, Aperture priority AE, Manual exposure, Custom (x2), Movie (Movie auto exposure, Movie manual exposure, Time-lapse movie)
Picture Styles	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)
Colour Space	Selectable between sRGB and Adobe RGB
Image Processing	Highlight Tone Priority Auto Lighting Optimizer (4 settings) Long exposure noise reduction Digital Lens Optimizer Peripheral illumination correction Distortion correction Chromatic aberration correction Diffraction correction Creative Assist: Base Style: Auto/Standard/Portrait/Landscape/Fine Detail/Neutral/ Faithful/ Monochrome/Picture Style File Monochrome (Sharpness Strength / Sharpness Fineness / Sharpness Threshold / Contrast (9 levels) / Filter effect (Ye - Yellow / Or - Orange / R - Red / G (Green) / Toning effect (S - Sepia / B - Blue / P - Purple / G - Green))
Drive modes	Single, High-Speed Continuous, Panning, Low-Speed Continuous, Self timer (2s, 10s, Custom, Remote)
Continuous Shooting	High-speed + (one-shot and Servo): 14 High-speed (one-shot and Servo): 7 Low-speed (one-shot and Servo): 3 RAW Burst mode: 23
Intervalometer	Time-Lapse Movie Mode

Technical Specifications

EOS M6 MARK II

Live View Mode	
Coverage	Approx. 100% (horizontally and vertically)
FILE TYPE	
Still Image Type	JPEG, RAW (CR3, a Canon 14-bit RAW format) * Raw images shot continuously are processed using 12-bit AD conversion
RAW+JPEG simultaneous recording	Yes, RAW + various JPEG compression possible
Image Size	L (Large): Approx 32.3MP (6960x4640) M (Medium): Approx 15.4 MP (4800x3200) S1 (Small 1): Approx 8.1MP (3472x2320) S2 (Small 2): Approx 3.8MP (2400x1600) RAW: Approx 32.3MP (6960x4640) C-RAW: Approx 32.3MP (6960x4640) *Rounded to the nearest 100,000 Aspect ratio: 3:2, 4:3, 16:9, 1:1 In-camera RAW processing & Image Resize available in playback
Movie Type	MP4 [Video: MPEG-4 AVC/H.264, variable (average) bit rate] Audio: AAC
Movie Size	4K – (29.97p/25.00p)/Standard (IPB) Approx 120Mbps/UHS-I, UHS Speed Class 3 or higher Full HD High Frame Rate – (119.88p/100.00p)/Standard (IPB) Approx 120Mbps/UHS-I, UHS Speed Class 3 or higher Full HD - (59.94p/50.00p)/Standard (IPB) Approx 60Mbps/SD Speed Class 10 or higher (29.97p/25.00p)/Standard (IPB) Approx 30Mbps/SD Speed Class 4 or higher (29.97p/25.00p)/Light (IPB) Approx 12Mbps/SD Speed Class 4 or higher HD – (59.94p/50.00p)/Standard (IPB) Approx 26Mbps/SD Speed Class 4 or higher 4K Time-Lapse Movie: (29.97p/25.00p). 40MB/s or faster (reading speed) Time-Lapse Movie: (29.97p/25.00p). 20MB/s or faster (reading speed)
Movie Length	Max duration 29min 59sec, Max file size 4GB
OTHER FEATURES	
Custom Functions	15 customisable buttons/ dials
Intelligent Orientation Sensor	Yes, with Image Rotate
Playback zoom	1.5x - 10x enabled
Display Formats	(1) Single image with information (toggle up to 8 options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/100 image, by shot date, by folder, by movies, by stills, by protected images, by rating)
Slide Show	Playback time: 1/2/3/5/10/20 seconds Repeat: On/Off Transition Effects: Off, Slide in 1/ Slide in 2/ Fade 1/2/3
Histogram	Brightness/ RGB
Highlight Alert	Yes
Image Erase/Protection	Erase: Single image, Selected images, Selected range, All images Protection: Selected images, Selected range, All images, Unprotect all images in folder/on card
Menu Categories	(1) Still photo shooting (2) Movie recording (3) Playback (4) Wireless settings (5) Function settings (6) Customization settings (7) My menu
Menu Languages	25 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Vietnamese, Hindi, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Indonesian and Japanese
Firmware Update	Firmware update possible by the user: Camera firmware Lens firmware External Speedlite firmware BR-E1 firmware
INTERFACE	
Transmission	Hi-Speed USB (2.0) (Micro USB connector)
Terminal Type	USB Type-C
Other	Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch) Bluetooth® (Specification version 4.1, Bluetooth low energy technology)

SUPPORTED OPERATING SYSTEM	
PC & Macintosh	Windows & Mac OS compatible
Sending images to smartphone	After establishing a Wi-Fi connection with the camera and your smartphone, images can be sent using the Canon Camera Connect App.
Cloud/ Utility	Upload photos direct from the camera to Web Services or utilize EOS Utility to send images to your computer.
SOFTWARE	
Image Processing	Digital Photo Professional
Other	Picture Style Editor, EOS Utility, Image Transfer Utility. Camera Connect app available on iOS and Android devices.
POWER SOURCE	
Batteries	1 x Rechargeable Li-ion Battery LP-E17
Battery life	Screen on: Approx 305 shots Viewfinder on: Approx 250 shots Eco mode/screen on: Approx 410 shots Movie recording time: Up to 2hr 25min Playback time: Approx 300min
Power saving	Display off (15, 30 sec or 1, 3, 5, 10, 30 mins) Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable) ECO mode
Power Supply & Battery Chargers	Battery charger LC-E17E In-camera battery pack charging with USB Power Adapter PD-E1
PHYSICAL SPECIFICATIONS	
Body Materials	Magnesium alloy and electrolytic zinc-coated steel sheet
Operating Environment	0 – 40 °C, 85% or less humidity
Dimensions (WxHxD)	119.6 x 70.0 x 49.2 mm
Weight (body only)	Approx. 408 g (CIPA testing standard, including battery and memory card)
ACCESSORIES	
All	Optional Electronic Viewfinder EVF-DC1, EVF-DC2 External Flash: EX and EL series Speedlites Speedlite Transmitter: ST-E3-RT/ ST-E2 Off-Camera Shoe Cord OC-E3 AC Power Source: AC adapter CA-PS700 and DC coupler DR-E17 AC adapter kit ACK-E17 Interface Cable: IFC-100U, IFC-400U External Microphone: DM-E1 Remote Switcher: RS-60E3 Timer Remote Controller: TC-80N3 Bluetooth Remote Control: BR-E1 Strap: EM-200DB